



LLC "RU SIE Agrinol"
 3A STROITELNAYA STR.,
 Berdyansk, Zaporozhie reg., Ukraine, 7110
 tel/fax +38 (06153) 60-600 (multichannel)

QUALITY PASSPORT No. 25333 dd 16.07.2015

Hydraulic oil
Agrinol Hydraulic lift-46



TS U 23.2-36451680-154:2010

Shelf life – 3 years from manufacturing date

Consignee:

Luboil OU

Quantity: 16 of 0,18 MT = 2,88 MT

INDEX NAME	NORM	In fact	Test method
		for batch No.	
		21 07.2015	
1 Kinematic viscosity at 40°C, mm ² /c, within	41-51	49,11	DSTU GUST 33
2 Viscosity index, not less than	130	145	DSTU GOST 25371
3 Acid number, mg KOH/g, within	0,5-1,0	0,97	GOST 5985
4 Open cup flash point, °C, not lower than	180	198	GOST 4333
5 Pour point, °C, not higher than	Minus 40	Minus 40	GUST 20287
6 Density at 20°C, kg/m ³ , not more than	890	865	GUST 3900
7 Color, CNT units, not more than	5,5	1,5	GUST 20284
8 Corrosive effect on metals	Pass	Pass	GOST 2917
9 Ash content, %, not more than	0,2	0,13	GUST 1461
10 Mass fraction of mechanical impurities, %, not more than	None	None	GUST 6370
11 Mass fraction of water, %, not more than	None	None	GUST 2477
12 Foaming tendency, cm ³ , not more than:			Acc. to p. 7.3.13 of TS
- at 24°C, sequence I	80	70	
- at 94°C, sequence II	100	80	
- at 24°C after testing at 94°C, sequence III	80	70	

Conclusion: product meets the requirements of TS U 23.2-36451680-154:2010

Head of Production Control Dept

Gorbacheva

